TWA 281÷1432 TT/H

A CLASS ENERGY EFFICIENCY AIRCOOLED LIQUID CHILLERS WITH AXIAL FANS, TURBOCOR (MAGNETIC LEVITATION) COMPRESSORS AND FLOODED SHELL AND TUBE EXCHANGER.

TURBOLINE

The innovative TWA 281÷1432 TT/H **TURBOLINE** units, with **HFO-R1234ze** refrigerant, are designed to provide an effective solution to highly selective system needs. The latest generation refrigerant HFO-R1234ze, with GWP<1 (Global Warming Potential), is the most environmentally sustainable refrigerant on the market, and meets the strictest international environmental regulations. Furthermore, thanks to Turbocor compressors, the units perform with top efficiency at partial loads, low inrush currents, an excellent silent functioning and reduced weight.
The use of TURBOCOR dynamic partial-load oil-free magnetic levitation compressors managed by the TURBOSOFT self-adaptive electronic control, of flooded shell & tube evaporator and innovative heat exchangers, traditional or Microchannel, results in a high energy efficiency with unequalled SEER/ESEER/IPLV values, with minimum water content, and an excellent silent functioning. Compared to traditional units, equipped with Screw compressors, TURBOLINE units have low operational costs during their entire operating period, even lower than 50%. Besides, the units are equipped with a WEB MONITORING system for the monitoring and remote management of the units through the GPRS/EDGE/3G/TCP-IP communication protocol. Users enabled to the use of this service can, by a dedicated Web page, have access to the Monitoring, Managing and Statistics activities.
Are available as option the new EC Inverter fans with high available static pressure and efficiency.

The units are already compliant to ErP 2021 European Regulations.

FROM 262 KW TO 1340 KW.

VERSION

TWA
Cooling only
TWA/MC
Cooling only with MICROCHANNEL coils

FEATURES

- Self-supporting galvanized steel frame protected with additional protection achieved via polyester powder painting.
- Semi-hermetic centrifugal compressors with dual Turbocor turbine, oil free, magnetic rising rotor, thermal protection, continuous capacity adjustment system thanks to built-in INVERTER, automatic anti-cavitation system. The power circuit of the compressor is fitted with a set of electrolytic condensers to control the rising in the event of a power failure, reactor for the power factor correction, EMI filter for electromagnetic compatibility.
- Axial fans directly coupled to an electric motor with external rotor.
- Condenser made of copper tube and aluminum finned coils or aluminium MICROCHANNEL coils.
- High efficiency flooded shell and tube type evaporator, with one or two independent circuits on the refrigerant side and one on the water side, complete with water differential pressure switch.
- Cooling circuit shut-off valves on suction, discharge and liquid line.
- Electronic expansion valve.
- Electronic high and low pressure gauges.
- HFO-R1234ze refrigerant.
- Electrical board includes: main on-off switch with door lock, fuses, electronic/digital overload device to protect the compressors and thermo-contacts for fans, interface relay and terminals for external connections.
- Condensing Control is included: electronic proportional device that ensures efficient and continuous functioning of the unit with outside air temperature down to –20 °C. It also allows to reduce the sound level especially at night. It consists of a fans speed controller with continuous speed regulation, high and low pressure transducers on cooling circuit and an electrical heater on electrical board.
- TURBOSOFT control and regulation system is fitted with RS485 serial interface and Web Monitoring device for remote monitoring via GPRS/EDGE/3G/TCP-IP network.

ACCESSORIES

FACTORY FITTED ACCESSORIES:

IM	Automatic circuit breakers
EC	EC Inverter fans
ECH	EC Inverter fans with high available static pressure
HR	Desuperheater
HRT/S	Total heat recovery in series
HRT/P	Total heat recovery in parallel
TX	Coil with pre-coated fins
TXB	Coil with epoxy treatment
EW	External water connections
PU	Single circulating pump
PD	Double circulating pump
FE	Antifreeze heater for evaporator
FX	Antifreeze heater for evaporator and pipes
FZ	Antifreeze heater for evaporator, single pump and pipes
FH	Antifreeze heater for evaporator, double pump and pipes
TS	Touch screen Interface
ISB	BACnet MSTP protocol, RS485 serial interface
ISBT	BACnet TCP/IP protocol, Ethernet port
ISL	LonWorks protocol, FTT-10 serial interface
IAV	Remote set-point, 0-10 V signal
IAA	Remote set-point, 4-20 mA signal
IAS	Remote signal for second set-point activation
IDL	Demand limit from digital input
CP	Potential free contacts

LOOSE ACCESSORIES:

MN	High and low pressure gauges
CR	Remote control panel
RP	Coils protection metallic guards
FP	Coils protection metallic guards with filter
AG	Rubber shock absorbers
AM	Spring shock absorbers
FL	Flow switch

TECHNICAL DATA - TWA 281÷1432 TT/H

MODEL			281	361	561	721	831	1071	1431	562	722	1432
Cooling STD version	Cooling capacity (1)	kW	262	335	524	670	777	1000	1340	524	670	1340
	Absorbed power (1)	kW	76	94	154	191	228	280	377	154	193	381
	EER (1)		3.45	3.56	3.40	3.51	3.41	3.57	3.55	3.40	3.51	3.55
Cooling STD version (EN14511)	Cooling capacity (1)	kW	261	334	522	668	774	997	1336	523	668	1335
	Absorbed power (1)	kW	77	95	156	193	231	283	381	155	195	386
	EER (1)		3.39	3.52	3.35	3.46	3.35	3.52	3.51	3.37	3.46	3.51
	ESEER		4.70	4.82	4.87	5.17	5.02	5.17	5.19	4.70	4.93	4.99
	EUROVENT Class		A	A	A	A	A	A	A	A	A	A
	SEER (2)		4.58	4.78	4.60	4.75	4.66	4.90	4.91	4.59	4.72	4.89
	Energy Efficiency (2)	%	180	188	181	187	183	193	193	181	186	193
Cooling MC version	Cooling capacity (1)	kW	262	335	524	670	777	1000	1340	524	670	1340
	Absorbed power (1)	kW	72	89	145	181	216	264	356	145	183	360
	EER		3.64	3.76	3.59	3.70	3.60	3.79	3.76	3.59	3.70	3.76
Cooling MC version (EN14511)	Cooling capacity (1)	kW	259	334	518	668	774	997	1336	519	668	1335
	Absorbed power (1)	kW	73	90	147	183	219	267	360	146	185	365
	EER (1)		3.55	3.71	3.52	3.65	3.53	3.73	3.71	3.55	3.65	3.71
	ESEER		4.92	5.06	5.12	5.42	5.26	5.43	5.44	4.93	5.17	4.99
	EUROVENT Class		A	A	A	A	A	A	A	A	A	A
	SEER (2)		4.82	5.04	4.88	5.00	4.92	5.18	5.19	4.87	4.96	5.16
	Energy Efficiency (2)	%	190	199	192	197	194	204	205	192	195	203
Compressor	Quantity	n°	1	1	2	2	3	3	4	2	2	4
	Refrigerant circuits	n°	1	1	1	1	1	1	1	2	2	2
	Capacity steps	n°	Stepless									
Evaporator	Water flow	l/s	12.52	16.01	25.04	32.01	37.12	47.78	64.02	25.04	32.01	64.02
	Pressure drops	kPa	40	47	47	50	40	43	32	47	50	32
	Water connections	DN	100	100	125	125	150	150	150	125	125	150
Electrical characteristics	Power supply	V/Ph/Hz	400/3/50									
	Max. running current	A	173	173	339	347	505	520	678	339	347	678
	Max. starting current	A	25	25	191	199	357	372	530	191	199	530
Unit with pump	Pump available static pressure	kPa	140	120	110	125	105	120	145	110	125	145
	Water connections	DN	100	100	150	150	150	150	200	150	150	200
Sound pressure	STD version (3)	dB(A)	70	70	71	71	71	71	72	71	71	72
	MC version (3)	dB(A)	69	69	70	70	70	70	71	70	70	71
Weights	Transport weight	Kg	2610	3000	4050	4460	6050	6820	8100	4290	4700	8400
	Operating weight	Kg	2670	3070	4150	4580	6210	7010	8400	4390	4820	8700

DIMENSIONS

MODEL			281	361	561	721	831	1071	1431	562	722	1432
L	STD/MC	mm	4000	5000	6200	7200	8400	10050	11700	6200	7200	11700
W	STD/MC	mm	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200
H	STD/MC	mm	2100	2100	2100	2100	2500	2500	2500	2100	2100	2500

CLEARANCE AREA

TWA 281÷1432 TT/H

500	1800	1000	1800

Electrical board side

NOTES

1. Chilled water from 12 to 7 °C, ambient air temperature 35 °C.
2. Seasonal energy efficiency of cooling at low temperature. According to EU Regulation n. 2016/2281.
3. Sound pressure level measured in free field conditions at 1 m from the unit. According to ISO 3744.

N.B. Data of MC version are specified on technical brochure.